


DYNAMO FEED INSTALLATION

D1000-1550 Cross Feed

Lagun Mills



PREPARATION

- Step 1:* Remove the nut, key, handle, and dial assembly from the lead screw.
- Step 2:* Remove the shroud from the power feed.
- Step 3:* Slide the spacer and bearing race onto the lead screw.
- Step 4:* Slide the power feed over the bearing race and square to the mill.
- Step 5:* Transfer the mounting holes from the power feed to the mill.
- Step 6:* Remove the power feed, spacer, and bearing race from the mill.
- Step 7:* Drill and tap 1/4-20 x 3/8" deep thread into the bearing housing. **Do not** contaminate the bearings.

POWER FEED INSTALLATION

- Step 1:* Screw the shaft extension onto the lead screw and tighten.
- Step 2:* Using the hole provided as a pilot, drill 1/8" diameter through the lead screw and pin the extension in place using the 1/8 diameter x 5/8" long roll pin. File smooth.
- Step 3:* Slide the spacer and bearing race onto the lead screw.
- Step 4:* Place the shroud onto the power feed and slide the unit onto the lead screw. Secure using 1/4-20 x 1-1/4" long socket head cap screws.

BEVEL GEAR INSTALLATION

- Step 1:* Turn the leadscrew CW to ensure the leadscrew is extended out fully and shouldered against the bearing
- Step 2:* Install two of the thickest shim washers, then the bevel gear. Measure the gap between the back face of the gear and the front face of the power feed, as shown in Fig.A. of the INSTALLATION & OPERATION MANUAL. Add, remove or replace shims to obtain the .080/.085 in. (2.0 / 2.16 mm) dimension. Install the spacer, handcrank, and nut. Check that the dimension is still ok after the nut is tightened.
- Step 3:* With feed in neutral, turn hand crank. If it turns freely in one direction but catches in the other, the backlash is too large. Reduce the thickness of the shims. If rough engagement is heard or felt in BOTH directions you need additional shims.

DIAL AND HANDWHEEL INSTALLATION

Step 1: After getting the proper backlash, the dial should be adjusted to obtain .005" spacing from the face of the power feed. This is important in order to keep chips from entering the gear train. Two plastic (.030" thick) and five brass (.005" thick) washers are provided for this. Shim as required.

Step 2: In the following sequence, put on the dial locking nut, place key in the shaft extension, and slide the handcrank #57903 in place. Secure with the 1/2-20 lock nut.

LIMIT SWITCH INSTALLATION

Refer to the D-1000Y INSTALLATION & OPERATION MANUAL

OPERATION

See INSTALLATION & OPERATION MANUAL

WARNINGS

Check hand crank clearances before operation.

Clearances between the surfaces of the hand crank and the non-moving parts of the equipment on which the hand crank is installed must be at least one-fourth inch (1/4") to prevent injury. Modification of existing hand crank or replacement may be required.

Do not operate without proper clearance!

Prevent contact during fast traverses.

SERVO PRODUCTS COMPANY

Web: www.servoproductsco.com

CALIFORNIA BRANCH

14254 Valley Blvd., Unit A
City of Industry, CA 91746
Ph. 626.961.7800 Fax 626.961.2444

HEADQUARTERS

34940 Lakeland Blvd.
Eastlake, OH 44095
Ph. 440.942.9999 Fax 440.942-9100

FLORIDA BRANCH

8950 131st Ave. N.
Largo, FL 33773
Ph. 727.585.8555 Fax 727.585.6555

